

HYDRAULIC CUT-OFF SAWS & GRINDERS



Stanley's line of cut-off saws and grinders accommodate almost any kind of cutting or grinding work from concrete or metal cutting to deburring and shaping to underwater cutting. All tools accept commonly available abrasive carbide and diamond, cutting and grinding accessories.

HYDRAULIC TOOLS & ACCESSORIES



GR31 Grinder



C025 Cut-off Saw



C025 w/optional Saw Cart (No. 33281)

SPECIFICATIONS

No.	Weight	Length	Width	Flow Range	Pressure	Rotation/RPM	Wheel Capacity
CO25141	20 lbs	21 in.	11 in.	7-9 gpm	1500-2000 psi	CCW/4500	14 in. --
CO25541	20 lbs	21 in.	11 in.	7-9 gpm	1500-2000 psi	CW/4500	14 in.
GR31101	12 lbs	8 in.	28 in.	7-9 gpm	1500-2000 psi	CCW/5800	9 in.

HYDRAULIC DIAMOND CHAIN SAWS

Stanley's diamond chain saws are light-weight and powerful and ideal for fast cutting of concrete, reinforced concrete, conduit, brick and other masonry. Plunge cutting is no problem. If you're involved in construction, remodeling, demolition, rescue, or water or sewer maintenance, you need one of these tools. Sealed saw chain requires less water pressure, from as low as 20 psi to 40-60 psi normally available from building water supply systems.



DS06



DS11

*Bar and Chain Not Included, see page 103.

SPECIFICATIONS

No.	Weight	Length	Width	Flow Range	Pressure	Cutting Capacity
DS063000	14 lbs	24 in.	9 in.	7-9 gpm	1000-2000 psi	8 in.
DS113000	26 lbs	38 in.	9 in.	7-9 gpm	1000-2000 psi	12, 15 in.

HYDRAULIC HAMMER & SINKER DRILLS


Wood or steel drilling, concrete core or hold drilling, or blast holes is no problem with Stanley's complete line of drills. Also take a look at Stanley's impact wrenches for drilling in wood utility poles and large timbers.



HD08 Hammer Drill



CD10 Core Drill



HD45 Hammer Drill



SK47 Sinker Drill

SPECIFICATIONS


No.	Weight	Length	Width	Flow Range	Pressure	Performance	Capacity	Misc.
HD08531G	6 lbs	13 in.	5-1/2 in.	3-9 gpm	750-2000 psi	1175 rpm @ 6 gpm	SDS Shk Plus	
HD45110B	45 lbs	22 in.	14 in.	7-9 gpm	1500-2000 psi	300 rpm	#736 Skil Hex	--
SK47130	52 lbs	23 in.	14 in.	7-9 gpm	1500-2000 psi	10 ft. Hole	7/8 in.x4-1/4 in. Hex Shank	Air Flush
CD10100	18 lbs	19 in.	4 in.	5-13 gpm	1000-2000 psi	380, 900 & 1800rpm	5/8 to 6 3/8 in. bits	Threaded

30 Travis Avenue, PO Box 1690, Binghamton, NY 13902-1690
Phone 607-773-2405 • Fax 607-773-2414 • www.linemenssupply.com

HYDRAULIC IMPACT WRENCHES

STANLEY[®]

Hydraulic powered impact wrenches are more powerful than air or electric impact wrenches which is evident with the Stanley model ID07, 1/2 inch impact wrench and drill, that develops up to 500 foot pounds of impact torque. Stanley's impact wrenches are available in a variety of models from 500 to 3500 foot pounds of impact torque with different anvil configurations.



IW16



ID07



IW12



IW24

HYDRAULIC
TOOLS &
ACCESSORIES

SPECIFICATIONS

No.	Weight	Length	Width	Flow Range	Pressure	Torque	Capacity
ID07810	7.2 lbs	8.5 in.	4.5 in.	4-12 gpm	750-2000 psi	500 ft lbs	7/16 in. Quick Change
IW12140	14 lbs	9 in.	4 in.	4-12 gpm	1000-2000 psi	250-1200 ft lbs	3/4 in. Square Drive
IW16150	26 lbs	14 in.	5 in.	7-12 gpm	1500-2000 psi	500-2500 ft lbs	1 in. Square Drive
IW24160	43 lbs	16 in.	5 in.	7-12 gpm	1800-2000 psi	800-3500 ft lbs.	1-1/2 in. Square Drive

HYDRAULIC TREE TRIMMING TOOLS

Stanley's line of tree-trimming tools offer a higher power-to-weight ratio than that of gasoline or electric powered tools. They are ideal for bucket truck use because of their compatibility with the bucket truck hydraulics. The CR27 Circle Saw features a blade brake that reduces the blade coast time to 2.5-5.0 seconds after release of the trigger. Stanley tree-trimming tools are used around the world by utility companies, professional tree-trimmers, landscapers.



CS23/CS26 Long Reach Chain Saw



CR27 Circular Saw



PR41 Pruner



CS05/CS06

SPECIFICATIONS

No.	Weight	Length	Width	Flow Range	Pressure	System Type	Capacity
CS05620	6.25 lbs	14 in.	9 in.	4-6 gpm	1500-2000 psi	OC/CC	15 in.
CS06620	6.25 lbs	14 in.	9 in.	7-9 gpm	1500-2000 psi	OC/CC	15 in.
CS23811	9 lbs	74 in.	6 in.	7-9 gpm	1500-2000 psi	OC/CC	12 in.
CS25811	11 lbs	90 in.	6 in.	4-6 gpm	1000-2000 psi	OC/CC	13 in.
CS25812	10.4 lbs	75 in.	6 in.	4-6 gpm	1000-2000 psi	OC/CC	13 in.
CS26811	9 lbs	74 in.	6 in.	3-5 gpm	1500-2000 psi	OC/CC	12 in.
CS28811	11 lbs	90 in.	6 in.	7-9 gpm	1000-2000 psi	OC/CC	13 in.
CS28812	10.4 lbs	75 in.	6 in.	7-9 gpm	1000-2000 psi	OC/CC	13 in.
CR27891	9.75 lbs	79 in.	9 in.	5-7 gpm	1500-2000 psi	OC/CC	9 in. dia. blade
PR41131	11.5 lbs	84 in.	6 in.	3-9 gpm	1000-2000 psi	OC	2.25 in.

30 Travis Avenue, PO Box 1690, Binghamton, NY 13902-1690
Phone 607-773-2405 • Fax 607-773-2414 • www.linemenssupply.com