



BUCK SQUEEZE WOOD POLE FALL PROTECTION SYSTEM

The BuckSqueeze Wood Pole Fall Protection System* fall protects line personnel from the ground to the elevated work position and back to the ground!

Benefits include:

- Wood pole fall protection during ascent and descent.
- Fall protection while climbing over obstacles.
- Ease of adjustment for the distance from the pole.
- Ease of adjustment for the diameter of the pole while ascending or descending.
- Rollers on the paddle tensioner and carabiner dee piece provide superior lateral movement.
- An oversized dee ring and specially designed carabiner make climbing over obstacles easy.

Accessories for the Bucksqueeze (Sold Separately)



8' Retractable Lanyard, Model 5008-80F+N, mounts on the body belt & secures the user when climbing over obstacles.



A second positioning strap, 48119Y (see page 16), can also be used to secure the user when climbing over obstacles.



The BuckTooth, Model 485, is an accessory that must be installed when climbing iced poles.

*Brings a user into compliance with OSHA 1910.269 (g)(2)(v) requirements.

BUCK TRAINER

The Buck Trainer is a reliable apprentice fall protection 5000 lb. anchor that rotates 250°. It can be attached to any pole up to a 9" diameter at any height by a qualified climber and a groundman. This unit is ideal to transport to remote areas to field test potential apprentices before sending them to the actual training facility.

Benefits and specifications of the Buck Trainer

- Fits a pole with diameter up to 9"
- Mounts anywhere on pole
- Rotates 250°
- Keeps climber 36" from pole
- Tested to 5000 lbs.

included

- Ratchet strap to lift Buck Trainer with handline
- Bolts and nuts
- Mounting brackets
- Carabiner to mount lifeline (5005L1)

*For Retractable Lifelines see page 18.



5204



BUCKSQUEEZE MODEL 483D

(For distribution poles up to a 50" circumference)

Friction Buckle to easily adjust for the distance from pole.

Locking Snap Hooks

Paddle Tensioner

CAM Buckle used to adjust for pole diameter.

Order 484T for transmission poles up to a 90" circumference.